Powerful Features with Simple Configurations





TeleEye RN680 Series

TeleEye RN680 Series covers a full range of feature-rich and easy-to-use 4-, 8- and 16- channel digital video recorders. With the MPEG-4 compression full-feature video recording, TeleEye RN680 Series guarantees smooth and crystal clear video quality on both live monitoring and recording.

TeleEye RN680 Series is designed to support up to 2 internal hard drives for enhancing the storage capacity and providing longer recording duration. Its built-in CD writer enables fast video footage extraction for evidential purpose.

TeleEye RN680 Series equips with powerful features and easy-to-use operation, and is suitable for a wide range of applications from retail outlet, factory, property management and public utilities installations.

Features

- 4, 8 or 16 video & alarm input models
- Resolution up to 720x576 / 720x480 pixels
- Video compression: MPEG-4
- Recording rate up to 100/120fps
- Simultaneous recording, playback & network operation
- Main monitor & call monitor output
- VGA output (optional)

- Support TCP/IP, DHCP & DDNS network
- Support up to 2 internal hard drives
- Built-in CD writer & USB interface for video extraction
- Schedule, alarm, motion detection & remote recording
- Fast & easy search for recorded video
- Accessible through web browser
- Telemetry control
- Administrator & access control



*Tele*Eye Group Hong Kong (Head Office)

Signal Communications Limited

China Tel: (86) 755 2671 2122 Email: info@TeleEye.com.cn Tel: (81) 42 742 2690 Email: info@CAMERIO.co.jp Japan Singapore Tel: (65) 6745 3921 Email: sales@TeleEye.com.sg U.K. Tel: (44) 1628 776061 Email: ukinfo@TeleEye.com

Croatia **Philippines** Mauritius

International: (852) 2995 5996 Fax: (852) 2995 5901 South Africa Tel: (27) 11 557 9200

Tel: (385) 52383101 Tel: (632) 3650897 Tel: (230) 686 5238

16/F, Millennium City 3, 370 Kwun Tong Road, Kowloon, Hong Kong Hong Kong: (852) 2995 5992 Email: info@TeleEye.com Email: info@TeleEye.co.za

Email: info@TeleEye.com.hr Email: contact@TeleEye.com.ph Email: info@TeleEye.com.mu

Features and specifications are subject to change without prior notice

Copyright© 2007 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries All other trademarks are the property of their respective owners. 2007.07

Specifications

MODEL		RN684 RN688		RN6816			
		VIDEO INPUT					
			(P): PAL/CCIR, 625 lines, 25 frames per second				
STANDARD		(N): NTSC/EIA, 525 lines, 30 frames per second					
		composite video, 1 Vp-p, BNC, switchable					
NO. OF CHANNELS		4	8	16			
	AIN MONITOR	VIDEO OUTPUT					
	MAIN MONITOR		BNC x I, I.0 Vp-p, 75ohm - BNC x I, I.0 Vp-p, 75ohm				
	ALL MONITOR	-					
Ve	GA (OPTIONAL)	800x600, 1024x768, 1280x1024 pixels					
		RECORDING					
MODE		Schedule, Motion, Alarm, Remote					
HD TYPE			DE interface, ATA66, 2 interna				
MAX. RECORDING RATE		D1 (PAL: 25fps at 720x576 pixels / NTSC: 20fps at 720x480 pixels)					
		Half D1 (PAL: 720x288 pixels / NTSC: 720x240 pixels) CIF (PAL: 100fps at 360x288 pixels / NTSC: 120fps at 360x240 pixels)					
PLAYBACK		IX, 2X, 4X, 8X, 16X, 32X					
		COMMUNICATION					
NETWORK		TCP/IP, DHCP, DDNS					
VIDEO COMPRESSION		MPEG-4, Advanced Simple Profile					
USB		Yes					
		EVENT HANDLING					
ALARM INPUTS / OUTPUTS		4 inputs, I output	8 inputs, I output	16 inputs, I output			
		POWER					
VOLTAGE		External Adapter, AC 100~240V to DC 12V					
MAX. RATING		96W					
		OPERATING ENVIRONMENT					
AMBIENT TEMPERATURE		0°C - 40°C					
RELATIVE HUMIDITY		30% ~ 90% (no condensation)					
		MECHANICAL DESIGN					
DIMENSION		440mm (W) x 50mm(H) x 340mm (D)					
NET WEIGHT		4.9kg					

Recording Duration (Days) of TeleEye RN688								
D1 (720 x 576 pixels)		HD1 (720 x 288 pixels)		CIF (36 pix	0 x 288 els)	- 8 cameras recording		
fps	Days	fps	Days	fps	Days	- HDD: 500GB - Moderate amount of motion - Best picture quality - Testing model: RN688		
25	12	50	7	100	9			
12	-	25	15	50	17			
8	29	8	36	8	54			

PC Requirements
CPU: Pentium IV 2GB or above
RAM: 512MB or above
OS: MS Windows 2000, XP



China

Japan

U.K.

Singapore

TeleEye Group Hong Kong (Head Office) Signal Communications Limited

Tel: (86) 755 2671 2122 Email: info@TeleEye.com.cn Tel: (81) 42 742 2690 Email: info@CAMERIO.co.jp Email: sales@TeleEye.com.sg Tel: (65) 6745 3921 Tel: (44) 1628 776061 Email: ukinfo@TeleEye.com

16/F, Millennium City 3, 370 Kwun Tong Road, Kowloon, Hong Kong Hong Kong: (852) 2995 5992 International: (852) 2995 5996 Fax: (852) 2995 5901 Email: info@TeleEye.com

South Africa Tel: (27) 11 5579200 Email: info@TeleEye.co.za Croatia Tel: (385) 52 383101 Email: info@TeleEye.com.hr **Philippines** Tel: (632) 3650897 Email: contact@TeleEye.com.ph Mauritius Tel: (230) 686 5238 Email: info@TeleEye.com.mu