



Features

- Vari-focal Auto Iris Lens
- 3x Digital Zoom (Continuous)
- 64 Preset Locations, 1 Patrol Sequence
- Auto Pan
- RS-485 Telemetry Interface
- Protocol Support: TeleEye DM4 and Pelco D



TeleEye DM-KB04

Specifications

MODEL	DM336P	DM336N
	VIDEO	
PICK UP DEVICE	1/3" interline transfer CCD	
PICTURE ELEMENTS	752 (H) x 582 (V)	768 (H) x 494 (V)
SENSING AREA	4.9mm x 3.7mm	
HORIZONTAL RESOLUTION	470TV lines	
LENS & VIEW ANGLE	f=4 ~ 9mm, F1.2 (viewing angle (H) = approx. 70.8° ~ 31.4°)	
MIN. ILLUMINATION	1.0 Lux	
WHITE BALANCE	Automatic	
ELECTRONIC SHUTTER	1/50 (1/60)	
S/N RATIO	More than 48dB	
	TELEMETRY CONTROL	
PAN	Range: 0° - 355°, Speed: 9° - 93° / sec	
TILT	Range: 5° - 90°, Speed: 9° - 93° / sec	
NO. OF PRESETS	64	
NO. OF PATROL SEQUENCES	1	
DATA RATE	2400, 4800, 9600bps (auto detection)	
DATA INTERFACE	RS-485	
PROTOCOL	TeleEye DM4, Pelco D	
	POWER & ENVIRONMENT	
VOLTAGE	12V DC, (max. 500mA)	
OPERATING TEMPERATURE	-10°C - 50°C	
HUMIDITY	0 ~ 80%	
	MECHANICAL DESIGN	
NET WEIGHT	600g	



Tele Eye Group
Hong Kong (Head Office)

Signal Communications Limited

16/F, Millennium City 3, 370 Kwun Tong Road, Kowloon, Hong Kong
 International: (852) 2995 5996 Hong Kong: (852) 2995 5992
 Fax: (852) 2995 5901 Email: info@TeleEye.com

China

Japan

Singapore

U.K.

Tel: (86) 755 2671 2122 Email: info@TeleEye.com.cn
 Tel: (81) 42 742 2690 Email: info@CAMERIO.com.jp
 Tel: (65) 6745 3921 Email: sales@TeleEye.com.sg
 Tel: (44) 118 953 3707 Email: ukinfo@TeleEye.com